



System Myers Sprayer – NR 6/3

Wanner Maschinenbau
Simoniusstraße 20
88239 Wangen i. Allgäu /
Germany

Tel.: (0 75 22) 93 10-0
Fax: (0 75 22) 2 21 79

info@wanner-maschinenbau.de



- Category 2 lower link hitch with one-sided wide angle PTO shaft
- 2 filler openings with sieve
- Hydraulic agitator - agitator tube and injector agitator can be switched off
- Flushing device
- Jetting-in device and tank gauge
- Suction filter with automatic shut-off
- Central pressure filter
- Electrical remote control; 4 boom sections with central switch-off, pressure setting, pressure indicator can be controlled from tractor on
- Electro-hydraulic control via joystick

Functions:

- Boom fold / extend system for transport or field position
- Lift mast
- Adjustment of the boom length according to row width
- Central On/off flow-control of the spray mixture.
- Radial blower with impeller diameter of 500 mm
Airflow rate: 33,000 / 38,000 m³/h with air feed to 6 sections with 3 air discharge openings each for the treatment of 3 rows complete
- Row distance from 1.60 to 3.20 m, adjustable manually
- Signal lights
- Single nozzles with drip-stop
- Hand wash tank
- Tank cleaning



H&W equipment
for vineyard & winery