

LIPCO

LIPCO GmbH Am Fuchsgraben 5b, D-77880 Sasbach/Germany Phone: 07841-209440 Fax: 07841-209442 e-mail: mail@lipco.com

TUNNEL - Sprayer Type TSG-N1-N2

Technical details:

- steel framework with double layer paintwork (red RAL 3002)
- hydraulic tunnel width adjustment with hydraulic cylinder
- 90° short turn hitch with in row hydraulic steering
- recycling walls PE with all-round spray collectors and hydro injector for recycling recovered spray.
- stainless steel jet pipe adjustable integrated in each recycling wall.
- Adjustable nozzle holder with diaphragm check valve , 5 per tunnel wall, single shut off, min. pressure 5 bar/75 PSI
- ALBUZ APE 80° orange fan spray nozzles.
- Flexible suspension on the outside wall to avoid machine and plant damage.
- Recycling filter, pressure filter and suction filter build in
- Electric controls for all functions, build in pressure gauge
- 160 liter (38 Gal.) diaphragm pump.
- PTO-Shaft
- 1000 liter / 238 Gal. spray tank with agitator and build in
- 100 liter/23 Gal. system cleaning tank.
- 15 liter / 3,5 Gal. clean water tank.
- Centre wheel Terra, 31x15.5x15: outside 185 R-14



Options:

- Air assistance
- Tunnel width adjustment 1,30 m / 4'4"
- External mixer
- Hydraulic height adjustment 30 cm / 1'
- Row width up to 3,00 m / 10'




Dimensions and Weight:

Tunnel length 1,25 m / 42 "
Max. total height (canapé) 2,20 m / 7' 8"
Tunnel width adjustment 0,20-1,10 m / 8" – 3'8"

Min width row: 1,60 m / 5" 4" single row unit
1,70 m / 5' 8" double row unit

Weight: 870 kg / 1920 lbs single row unit
1100 kg / 2425 lbs double row unit

Hydraulic: 1 Double hydraulic valve, additional single valve and non pressurized return line required for air assistance.



H&W equipment
for vineyard & winery