

LIPCO

LIPCO GmbH Am Fuchsgraben 5b, D-77880 Sasbach/Germany Phone: 07841-209440 Fax: 07841-209442 e-mail: mail@lipco.com

TUNNEL - Sprayer Convertor-Kit TSG-U

Technical details:

- Steel framework with double layer paintwork (red RAL 3002)
- Hydraulic tunnel width adjustment with hydraulic cylinder
- Recycling walls PE with all-round spray collectors and hydro injector for recycling recovered spray.
- Stainless steel jet pipe adjustable integrated in each recycling wall.
- Adjustable nozzle holder with diaphragm check valve , 5 per tunnel wall, single shut off, min. pressure 5 bar/75 PSI
- ALBUZ APE 80° orange fan spray nozzles.
- Flexible suspension on the outside wall to avoid machine and plant damage.
- Hose kit with pressure and recycling hose
- Recycling filter, pressure filter and suction filter build in



Options:


- Air assistance
- Tunnel width adjustment 1,30 m / 4'4"
- Mid mount adaptor frame for tractor
- Pre manufactured adapter frame
- Hydraulic height adjustment

Dimensions and Weight:

Tunnel length 1,25 m / 42 "
Max. total height (canapé) 2,20 m / 7' 8"
Tunnel width adjustment 0,20-1,10 m / 8" - 3'8"

Min width row: Width of tractor / pull behind sprayer
or 3 Pt-hitch sprayer
+ 0,80 m / 2'8" / single row set up
+ 1,20 m / 4' / double row set up

Weight: 120 kg / 265 lbs
Hydraulic: 1 Double hydraulic valve, additional single valve and non pressurized return line required for air assistance.



H&W equipment
for vineyard & winery

Niagara on the Lake, ON phone: (905) 468-5016, fax: (905) 468-5676, e-mail: info@vineyardmachines.com