



Rotary harrow SKE



Pairs of rotary units running in opposite make for smooth running free of lateral traction. Perfect soil leveling will be guaranteed.


Standard equipment:

Solid construction, transmission pan made of silicon titanium steel-plate alloy, coated front wheels and large taper roller bearings in cast iron carters mounted at large pitch, heavy transmission for power take-off shaft with 540 revs/min., cutting tines made of coated special steel make for good pulverizing, spring mounted lateral baffle plates adjustable in height, dozer rail in front, adjustable in height, tubular king roll without center axle, mounting bolt, cat. 1, adjustable in height

Optional equipment upon request:

- Rear and front add-on unit
- Tubular king roll
- Pre-cultivator with 2 tines and holder
- Add-on unit - seed drill FGF 800
- Metal sheet protection for drive chain
- Cardan shaft with overload protection

Typ	Width/m	Working width/ m	Rotary Units	Weight in kg	Tractor HP
SKE 1000	1,03	1,00	4 Unit	370	20 - 44
SKE 1150	1,15	1,13	4 Unit	390	22 - 44
SKE 1300	1,30	1,28	6 Unit	450	25 - 44
SKE 1400	1,42	1,40	6 Unit	460	30 - 52
SKE 1500	1,50	1,48	6 Unit	470	30 - 52
SKE 1750	1,75	1,73	6 Unit	490	40 - 59
SKE 2000	2,03	2,00	8 Unit	560	45 - 65



H&W equipment
for vineyard & winery